

View Online at <https://aerobasegroup.com/nsn/6665-00-169-1447>

**Dc Voltage Rating:**

28.0 volts

**Usage Design:**

Field

**Component And Quantity:**

Oalarm unit, chemical agent automatic alarm, m42 /fsn6665-859-2215/, 1, battery, dry /ba3517/, /fsn6135-450-3528/, 1, battery, dry /ba3202/, /fsn6135-935-8738/, 4, detector unit, chemical agent automatic alarm m43 /fsn6665-859-2201/, 1, installation kit, chemical agent automatic alarm /for truck, utility, 1/4 ton/ /fsn6665-479-2716/, 1, mounting kit, chemical agent automatic alarm, m228 /high profile/ /fsn6665-859-2212/, 1, refill kit, chemical agent automatic alarm, m229 /fsn6665-859-2214/, 1

**Internal Battery Accommodation:**

Not included

**Specific Usage Design:**

Samples air continuously, which is automatically heated /if necessary/, filtered, drawn into the detector cell where it passes through the electrolyte solution. If v or g agent are present, the galvanic voltage produced by the cell increases. The change is amplified by the electronic module which sounds the detector horn and/or activates a flashing light, applies power to the remote terminals and stops the pump motor, the horn will continue to sound and/or the light flash until the detector is reset or disconnected by the operator. The system is designed for manpack and vehicular application using dry cell battery for manpack and mounting kit and installation kit for 1/4 ton utility truck appl

**Indicator Type:**

Flashing red light and horn

**Design Type:**

Nontripod mounting

**Media Detected:**

G chemical agent

**Special Features:**

Also detects v chemical agent and can be used on vehicles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T394-a