

View Online at <https://aerobasegroup.com/nsn/6665-01-161-4811>

Overall Height:

13.500 inches

Case Material:

Steel

Detecting Element Type:

Electrochemical

Detecting Element Detachability:

Integral

Voltage Rating:

120.0 volts

Preamplifier:

Not included

Photomultiplier:

Not included

Connector:

Included

Cable:

Not included

Special Features:

Monitor can be wall mounted; sealed case; has visual alarm, bright red, located on front panel; audible alarm emits shrill noise; also sounds if sensor disconnected for 30 seconds or more while unit is on and powered; amber pilot light indicates unit is on and powered; horn silence/reset switch cancels audible horn alarm; spdt warning relay for external use-trip point may be set for any range value; two spdt alarm relays, one latching, one nonlatching; power selector switch, permits use of 115 or 120 vac power, prewired 115 vac power cord supplied; includes circuit breaker reset; flow failure switch activates audio and visual alarm when flow to monitor interrupted; 3 way valve allows introduction of calibration gas; includes pressure relief valve; range 0-100 ppm co; weight 18 lbs

Functional Description:

Carbon monoxide air line monitor that continuously monitors compressed air lines for carbon monoxide; provides direct linear readout of co concentration, actuates alarms when predetermined level reached or sample flow to the unit stops

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T132-a