Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-009-0664

| | edia For Which Designed: |
|-----|--|
| | olanol 20 |
| | et Connection Type: |
| | readed |
| | d Application: |
| | /alq-119v12 5865-00-599-3253 pod, electronic countermeasures |
| | egral Relief Valve: |
| | tincluded |
| | eter Type: |
| Flo | |
| De | sign Type: |
| Са | se |
| Un | it Type: |
| Мс | punted |
| Sc | ale Quantity: |
| 1 | |
| Co | instruction: |
| Inc | losed w/sight window |
| Οι | Itlet Connection Type: |
| Th | readed |
| Sc | ale Marking: |
| Gp | m |
| Sc | ale Type: |
| Dir | ect capacity reading |
| Flo | pat Quantity: |
| 1 | |
| Tu | be Material: |
| Gla | ass |
| Mo | ounting Method: |
| Flu | ish panel |
| Ca | rrying Handle: |
| No | t included |
| Dia | al Scale Marking Range: |
| +0 | .0 to 4.0 |
| Οι | Itlet Connection Size: |
| 0.7 | 750in. Npt |
| Ba | se: |
| No | t included |
| Flo | pat Type: |
| Gι | ided |
| Flo | pat Material: |

NSN 6680-00-009-0664

