## NSN 6680-00-019-0529

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-00-019-0529



**Overall Length:** 5.375 inches Media For Which Designed: Air or water **Inlet Connection Type:** Threaded **End Application:** Poseidon **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Open front **Outlet Connection Type:** Threaded Scale Marking: Gal per hr Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass, borosilicate **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.0 to 10.0 **Outlet Connection Size:** 0.125 npt Base: Not included Float Type: Free

## NSN 6680-00-019-0529

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Glass or steel, stainless
Integral Heat Source:
Not included
Maximum Working Pressure:
200.0 pounds per square inch
Inlet Connection Size:
0.125 npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
2 gph
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Max operating temp 200 degrees f; size 4; no. Bj-5 float; one additional scale marking cubic ft per hr
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t