Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-019-0529

Overall Length:		
5.375 inches		
Media For Which Designed	:	
Air or water		
Inlet Connection Type:		
Threaded		
End Application:		
Poseidon		
Integral Relief Valve:		
Not included		
Meter Type:		
Float		
Design Type:		
Case		
Unit Type:		
Mounted		
Scale Quantity:		
1		
Construction:		
Open front		
Outlet Connection Type:		
Threaded		
Scale Marking:		
Gal per hr		
Scale Type:		
Direct capacity reading		
Float Quantity:		
1		
Tube Material:		
Glass, borosilicate		
Mounting Method:		
Direct line		
Carrying Handle:		
Not included		
Dial Scale Marking Range:		
+0.0 to 10.0		
Outlet Connection Size:		
0.125 npt		
Base:		
Not included		
Float Type:		

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Glass or steel, stainless
Integral Heat Source:
Not included
Maximum Working Pressure:
200.0 pounds per square inch
Inlet Connection Size:
0.125 npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
2 gph
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Max operating temp 200 degrees f; size 4; no. Bj-5 float; one additional scale marking cubic ft per hr
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t