NSN 6680-00-060-5303

Beaded tube

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-060-5303 **Overall Length:** 39.430 inches Media For Which Designed: Lubricating oil **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.21 to 6.40 **Outlet Connection Size:** 1-1/4 in. Tube od Base: Not included Float Type: Guided Float Material: Steel, corrosion resisting **Guide Type:**

NSN 6680-00-060-5303Flow Rate Indicating Meter - Page 2 of 2



Integral Heat Source:
Not included
Maximum Working Pressure:
90.0 pounds per square inch
Inlet Connection Size:
1-1/4 in. Tube od
Metering Tube Quantity:
2
Dial Scale Smallest Increment:
0.001 gpm
Dial Scale Reference Pointer:
Not included
Float Quantity Per Tube:
1
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Cpzf, awgj, apsj, ateq, ackl, astw, bhby, cpzj, cpzk, w/scales calibrated for mil-l-7808 lube oil at 100 degrees f
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t