

NSN 6680-00-060-5304 Flow Rate Indicating Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-060-5304 **Overall Length:** 39.430 inches Media For Which Designed: Lubricating oil **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: 2 **Tube Material:**

Glass

Mounting Method:

Flush panel

Carrying Handle:

Not included

Dial Scale Marking Range:

+0.4 to 13.0

Outlet Connection Size:

1.250 in. Tube od size

Base:

Not included

Float Type:

Guided

Float Material:

Steel, corrosion resisting

NSN 6680-00-060-5304Flow Rate Indicating Meter - Page 2 of 2



Guide Type:
Beaded tube
Integral Heat Source:
Not included
Maximum Working Pressure:
90.0 pounds per square inch
Inlet Connection Size:
1.250 in. Tube od size
Metering Tube Quantity:
2
Dial Scale Smallest Increment:
0.001 gpm
Dial Scale Reference Pointer:
Not included
Float Quantity Per Tube:
1
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
As differentiated by metering tue quantity, tube material, scale quantity, scale type, media for which designed, scale marking, dial scale
marking range, dial range, dial scale smallest increment and dial scale reference pointer
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filig:
T134-t