## NSN 6680-00-061-8039

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-061-8039 **Overall Length:** 5.750 inches Media For Which Designed: Water **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Open front **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +1.0 to 4.0 **Outlet Connection Size:** 1/2 in. Npt Base: Not included Float Type: Free

Float Material:

**Brass** 

## **NSN 6680-00-061-8039**Flow Rate Indicating Meter - Page 2 of 2



ntegral Heat Source:
Not included
Maximum Working Pressure:
175.0 pounds per square inch
nlet Connection Size:
1/2 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
D.20gpm
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
ntegral Pulsation Dampener:
Not included
nlet Connection Position For Which Designed:
Vertical
Outlet Connection Position For Which Designed:
Vertical
Alarm Signal:
ncluded
Reference Number Differentiating Characteristics:
Apsj, ateq, ackl, astw, cpzg, cpzh, bhby, aewh, cpzj, cpzk, awae, cpzl, bjdm, cpzm, bhsq, bmhw, abhp, acqw, cpzd, cpzp, cpzq, arth, bhcm,
cpzr and cpzs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
Γ134-t