NSN 6680-00-089-2005

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-089-2005	
Thread Class:	
2b second end	
Thread Direction:	
Right-hand both ends	
Overall Length:	
78.656 inches	
Thread Depth:	
0.375 inches second end	
Tip Length:	
0.950 inches and 1.010 inches second end	
Core Material:	
Steel	
Screw Thread Series Designator:	
Uns first end	
Core Surface Treatment:	
Cadmium plated	
Core Diameter:	
0.150 inches	
Thread Location:	
Internal both ends	
End Type:	
Square male second end	
Width Across Flats:	
1.000 inches first end	
End Connection Type:	
Threaded internal both ends	
Setscrew:	
Not included both ends	
Casing Material:	
Rubber and steel	
Wrenching Facility Type:	
Hexagon both ends	
Cross Costion Circ And Locations	

Cross Section Size And Location:

0.153 inches diameter first end

Casing Surface Treatment:

Any acceptable

Casing Length Between Ferrules:

Between 77.438 inches and 77.562 inches

Casing Outside Diameter:

Between 0.300 inches and 0.500 inches

Casing Protective Device Type:

Plastic cover or rubber cover

NSN 6680-00-089-2005Flexible Shaft Assembly - Page 2 of 2



Swivel End:
Not provided both ends
Enddiameter:
1.188 inches first end
Lubrication Fitting:
Not provided both ends
Corelength:
78.656 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Special Features:
Counterclockwise core rotation direction
Specification Or Standard:
1 class and b group and 1 type
Fsc Application Data:
Tachometer
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T246-e