# NSN 6680-00-089-2005

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-089-2005

Thread Class:
2b second end
Thread Direction:
Right-hand both ends
Overall Length:
78.656 inches
Thread Depth:
0.375 inches second end
Tip Length:
0.950 inches and 1.010 inches second end
Core Material:
Steel
Screw Thread Series Designator:
Uns first end
Core Surface Treatment:
Cadmium plated
Core Diameter:
0.150 inches
Thread Location:
Internal both ends
End Type:
Square male second end
Width Across Flats:
1.000 inches first end
End Connection Type:
Threaded internal both ends
Setscrew:
Not included both ends
Casing Material:
Rubber and steel
Wrenching Facility Type:
Hexagon both ends
Cross Section Size And Location:
0.153 inches diameter first end
Casing Surface Treatment:
Any acceptable
Casing Length Between Ferrules:
Between 77.438 inches and 77.562 inches
Casing Outside Diameter:
Between 0.300 inches and 0.500 inches
Casing Protective Device Type:
Plastic cover or rubber cover

## NSN 6680-00-089-2005

Flexible Shaft Assembly - Page 2 of 2

Swivel End:

Not provided both ends

Enddiameter:

1.188 inches first end

Lubrication Fitting:

Not provided both ends

Corelength:

78.656 inches

#### Core Rotation Direction:

Clockwise

Core Removability:

Removable

**Special Features:** 

Counterclockwise core rotation direction

#### **Specification Or Standard:**

1 class and b group and 1 type

#### **Fsc Application Data:**

Tachometer

Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

Deminiarization

No

### Fiig:

T246-e

