NSN 6680-00-091-9718

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-091-9718 **Thread Class:** 2b both ends **Thread Direction:** Right-hand both ends **Overall Length:** 181.125 inches Thread Depth: 0.375 inches both ends Tip Length: 0.700 inches and 0.950 inches first end **Core Material:** Steel **Screw Thread Series Designator:** Uns first end **Core Diameter:** 0.150 inches **Thread Location:** Internal both ends **End Type:** Square male second end Width Across Flats: 1.000 inches first end **End Connection Type:** Threaded internal both ends Setscrew: Not included both ends **Casing Material:** Rubber Wrenching Facility Type: Hexagon both ends **Cross Section Size And Location:** 0.150 inches diameter and 0.153 inches diameter first end **Torsional Deflection Rating:** Not rated **Casing Surface Treatment:**

Galvanized **Casing Length Between Ferrules:** 180.000 inches **Casing Outside Diameter:** 0.445 inches **Casing Protective Device Type:** Rubber cover

NSN 6680-00-091-9718

Flexible Shaft Assembly - Page 2 of 2



Lubrication Fitting:
Not provided both ends
Corelength:
Between 180.960 inches and 181.370 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
5.000 inches
Departure From Cited Document:
As modified by Ig between ferrules
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T246-e