

View Online at <https://aerobasegroup.com/nsn/6680-00-112-0227>

**Thread Class:**

2b both ends

**Thread Direction:**

Right-hand both ends

**Overall Length:**

96.125 inches

**Thread Depth:**

0.375 inches second end

**Tip Length:**

0.950 inches and 1.010 inches second end

**Shank Outside Diameter:**

Any acceptable both ends

**Core Material:**

Steel

**Screw Thread Series Designator:**

Uns first end

**Core Surface Treatment:**

Cadmium or zinc plated

**Core Diameter:**

0.150 inches

**Thread Location:**

Internal both ends

**End Type:**

Square male second end

**Width Across Flats:**

1.000 inches first end

**End Connection Type:**

Threaded internal both ends

**Setscrew:**

Not included both ends

**Casing Material:**

Rubber and steel

**Wrenching Facility Type:**

Hexagon both ends

**Cross Section Size And Location:**

0.150 inches diameter and 0.153 inches diameter first end

**Casing Surface Treatment:**

Any acceptable

**Casing Length Between Ferrules:**

90.000 inches

**Casing Outside Diameter:**

Between 0.300 inches and 0.500 inches

**Casing Protective Device Type:**

Plastic cover or rubber cover

**Swivel End:**

Not provided both ends

**Enddiameter:**

1.188 inches first end

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

96.125 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Removable

**Minimum Operating Radius:**

5.000 inches

**Special Features:**

Counterclockwise core rotation direction. Torsional strength in both directions 15.0 lbs. Thread size is 5/8-18 and 7/8-18. Cadmium or zinc plated.

**Specification Or Standard:**

1 class and a group and i type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T246-e