## NSN 6680-00-140-7544



Flow Rate Indicating Meter - Page 1 of 3

View Online at https://aerobasegroup.com/nsn/6680-00-140-7544

Media For Which Designed:
Liquid hydrogen
Inlet Connection Type:
Flange
Inlet Bolt Hole Quantity:
4
Inlet Bolt Hole Diameter:
0.625 inches
Inlet Bolt Circle Diameter:
2.625 inches
Integral Relief Valve:
Not included

Meter Type:
Float

Design Type:
Case
Unit Type:

Mounted
Scale Quantity:

Construction:

Inclosed w/sight window

**Outlet Connection Type:** 

Flange

Scale Marking:

Std cu ft per hr

Scale Type:

Direct capacity reading

Float Quantity:

1

**Tube Material:** 

Glass

**Mounting Method:** 

Flush panel

**Carrying Handle:** 

Not included

**Dial Scale Marking Range:** 

+240.0 to 2400.0

**Outlet Connection Size:** 

0.500 in. lps

**Outlet Bolt Circle Diameter:** 

2.625 inches

## NSN 6680-00-140-7544

Flow Rate Indicating Meter - Page 2 of 3



Outlet Bolt Hole Quantity:
4
Outlet Bolt Hole Diameter:
0.625 inches
Base:
Not included
Float Type:
Free
Float Material:
Steel, stainless
Integral Heat Source:
Not included
Maximum Working Pressure:
275.0 pounds per square inch
Inlet Connection Size:
0.500 in. lps
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
200 cu ft
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Serial no. 6904-65522
Reference Number Differentiating Characteristics:
As differentiated by special features
Shelf Life:
N/a
Unit Of Measure:

## NSN 6680-00-140-7544

Flow Rate Indicating Meter - Page 3 of 3



Demilitarization:

No

Fiig:

T134-t