NSN 6680-00-159-2239

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-159-2239 Media For Which Designed: Air **Inlet Connection Type:** Threaded **End Application:** Test stand **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Illuminative Method:** Incandescent lamp **Construction:** Side plate **Outlet Connection Type:** Threaded Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass, borosilicate **Mounting Method:** Flush panel **Carrying Handle:** Not included **Outlet Connection Size:** 0.750 in.Npt Base: Not included Float Type: Free Float Material:

Steel, federal standard 66, aisi 316/sae 30316

Integral Heat Source:

Not included

NSN 6680-00-159-2239

Flow Rate Indicating Meter - Page 2 of 2



Maximum Working Pressure:
100.0 pounds per square inch
Inlet Connection Size:
0.750 in. Npt
Metering Tube Quantity:
1
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Vertical
Outlet Connection Position For Which Designed:
Vertical
Alarm Signal:
Not included
Special Features:
0.02 to 0.20 lbs per min range of detachable scale; meter serial no. 6908-73653
Reference Number Differentiating Characteristics:
As differentiated by special features
Shelf Life:
<u> </u>
N/a
N/a
N/a
N/a Unit Of Measure:
N/a Unit Of Measure: Demilitarization: