

NSN 6680-00-169-6166 Liquid Volumetric Positive Displacement Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-169-6166 **Body Material:** Bronze **Maximum Operating Pressure:** 150.0 pounds per square inch Media For Which Designed: Water, cold **Inlet Connection Type:** Threaded **Maximum Operating Temp:** 120.0 degrees fahrenheit Installation Design: Direct mount **Inlet Connection Size:** 0.750 in. lps **Measurement Unit:** Gallon Scale Measurement Range: +0.0 to 9.9 **Outlet Connection Type:** Threaded **Smallest Increment Indicated:** 1.00 **Displacement Type:** Disk **Installation Location:** Any acceptable **Liquid Flow Rate:** 20.0 gallons per minute **Register Type:**

Dial w/pointer or wheel

Reset Feature:

Not provided

Printing Mechanism:

Not provided

Inlet Union Connection:

Not provided

Outlet Connection Size:

0.750 in. lps

Outlet Union Connection:

Not provided

Special Features:

Additional scale measurement range 0.0 to 999990.0

NSN 6680-00-169-6166

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T134-d