Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-169-6166

Pody Material:
Body Material: Bronze
Maximum Operating Pressure:
150.0 pounds per square inch
Media For Which Designed:
Water, cold
Inlet Connection Type: Threaded
Maximum Operating Temp:
120.0 degrees fahrenheit
Installation Design: Direct mount
Inlet Connection Size:
0.750 in. lps Measurement Unit:
Gallon
Scale Measurement Range: +0.0 to 9.9
Outlet Connection Type:
Threaded
Smallest Increment Indicated:
1.00
Displacement Type:
Disk
Installation Location:
Any acceptable
Liquid Flow Rate:
20.0 gallons per minute
Register Type:
Dial w/pointer or wheel
Reset Feature:
Not provided
Printing Mechanism:
Not provided
Inlet Union Connection:
Not provided
Outlet Connection Size:
0.750 in. lps
Outlet Union Connection:
Not provided
Special Features:
Additional scale measurement range 0.0 to 999990.0

## NSN 6680-00-169-6166

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

T134-d