

NSN 6680-00-174-6135 Liquid Volumetric Positive Displacement Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-174-6135 **Body Material:** Bronze **Maximum Operating Pressure:** 50.0 pounds per square inch Media For Which Designed: Water, hot **Inlet Connection Type:** Threaded **Maximum Operating Temp:** 180.0 degrees fahrenheit Installation Design: Direct mount **Inlet Connection Size:** 1.000 in. lps **Measurement Unit:** Us gallon Scale Measurement Range: +0.0/+10.0 **Outlet Connection Type:** Threaded **Displacement Type:** Disk **Installation Location:** Left hand side or right hand side **Liquid Flow Rate:** 18.0 gallons per minute **Register Type:** Dial w/pointer or wheel **Reset Feature:** Not provided

Printing Mechanism:

Not provided

Inlet Union Connection:

Provided

Outlet Connection Size:

1.000 in. lps

Outlet Union Connection:

Provided

Special Features:

Additional scale measurement range 0.0 to 9999990.0

Specification Or Standard:

B class

NSN 6680-00-174-6135

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



Shelf Life:			
N/a			
Unit	Of I	Vlea	asure:

Demilitarization:

No

Fiig:

T134-d