Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-174-6135

Body Material:
Bronze
Maximum Operating Pressure:
50.0 pounds per square inch
Media For Which Designed:
Water, hot
Inlet Connection Type:
Threaded
Maximum Operating Temp:
180.0 degrees fahrenheit
Installation Design:
Direct mount
Inlet Connection Size:
1.000 in. lps
Measurement Unit:
Us gallon
Scale Measurement Range:
+0.0/+10.0
Outlet Connection Type:
Threaded
Displacement Type:
Disk
Installation Location:
Left hand side or right hand side
Liquid Flow Rate:
18.0 gallons per minute
Register Type:
Dial w/pointer or wheel
Reset Feature:
Not provided
Printing Mechanism:
Not provided
Inlet Union Connection:
Provided
Outlet Connection Size:
1.000 in. lps
Outlet Union Connection:
Provided
Special Features:
Additional scale measurement range 0.0 to 9999990.0
Specification Or Standard:

B class

NSN 6680-00-174-6135

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T134-d