Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-174-6145

Body Material:	
Bronze	
Maximum Operating Pressure:	
100.0 pounds per square inch	
Media For Which Designed:	
Water, cold	
Inlet Connection Type:	
Threaded	
Maximum Operating Temp:	
100.0 degrees fahrenheit	
Installation Design:	
Direct mount	
Inlet Connection Size:	
0.750 in. lps	
Measurement Unit:	
Us gallon	
Scale Measurement Range:	
+0.0/+10.0	
Outlet Connection Type:	
Threaded	
Displacement Type:	
Disk	
Installation Location:	
Left hand side or right hand side	
Liquid Flow Rate:	
34.0 gallons per minute	
Register Type:	
Dial w/pointer or wheel	
Reset Feature:	
Not provided	
Printing Mechanism:	
Not provided	
Inlet Union Connection:	
Provided	
Outlet Connection Size:	
0.750 in. lps	
Outlet Union Connection:	
Provided	
Product Name:	
Meter, volumetric positive displac	ement liquid, class a, size 3/4 inch
Special Features:	•
Additional scale measurement ra	nge 0.0 to 9999990.0

## NSN 6680-00-174-6145

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



**Specification Or Standard:** 

A class

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

T134-d