NSN 6680-00-174-6146

Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-174-6146 **Body Material:** Bronze **Maximum Operating Pressure:** 100.0 pounds per square inch Media For Which Designed: Water, cold **Inlet Connection Type:** Threaded **Maximum Operating Temp:** 100.0 degrees fahrenheit Installation Design: Direct mount **Inlet Connection Size:** 1.000 in. lps **Measurement Unit:** Us gallon Scale Measurement Range: +0.0/+10.0 **Outlet Connection Type:** Threaded **Displacement Type:** Disk **Installation Location:** Left hand side or right hand side **Liquid Flow Rate:** 53.0 gallons per minute **Register Type:** Dial w/pointer or wheel **Reset Feature:** Not provided **Printing Mechanism:** Not provided **Inlet Union Connection:** Provided **Outlet Connection Size:** 1.000 in. lps **Outlet Union Connection:** Provided **Product Name:** Meter, volumetric positive displacement liquie, class a, size 1 inch

Special Features:

Additional scale measurement range 0.0 to 9999990.0

NSN 6680-00-174-6146

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



Specification Or Standard:
A class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T134-d