NSN 6680-00-174-6147

Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-174-6147 **Body Material:** Bronze **Maximum Operating Pressure:** 100.0 pounds per square inch Media For Which Designed: Water, cold **Inlet Connection Type:** Drilled flange **Maximum Operating Temp:** 100.0 degrees fahrenheit Installation Design: Direct mount **Measurement Unit:** Us gallon **Scale Measurement Range:** +0.0/+99999990.0 **Outlet Connection Type:** Drilled flange **Displacement Type:** Disk **Installation Location:** Left hand side or right hand side **Liquid Flow Rate:** 150.0 gallons per minute **Register Type:** Dial w/pointer or wheel **Reset Feature:** Not provided **Printing Mechanism:** Not provided **Outlet Connection Size:** 2.0 in. lps **Outlet Bolt Hole Quantity: Outlet Union Connection:** Not provided **Special Features:** Class a, size 2 inch (volumetric flow measurement of cold fresh water up to 100 degrees fahreheit (f) **Specification Or Standard:** A class Shelf Life:

N/a

NSN 6680-00-174-6147

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

T134-d