NSN 6680-00-176-5378

Overall Length:

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-00-176-5378



9.500 inches **Inlet Connection Type:** Threaded **Integral Relief Valve:** Included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Type: Millimeter reference reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Unit Location:** Upper center front **Dial Scale Marking Range:** +2.0 to 22.0 **Outlet Connection Size:** 1/4 in. lps Base: Not included Float Type: Free Float Material: Glass **Integral Heat Source:** Not included

NSN 6680-00-176-5378

Flow Rate Indicating Meter - Page 2 of 2



Maximum Working Pressure:
200.0 pounds per square inch
Inlet Connection Size:
1/4 in. lps
Metering Tube Quantity:
1
Maximum Water Capacity In Gallons Per Minute:
530.0
Maximum Air Capacity In Cubic Feet Per Minute:
22000.0
Dial Scale Smallest Increment:
200cc
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Cpzh, ateq and bhby
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t