## NSN 6680-00-217-6868

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-217-6868 **Overall Length:** 7.750 inches Media For Which Designed: Water **Inlet Connection Type:** Threaded **End Application:** Flow system sps33-4; uss long beach **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Side plate **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass, borosilicate **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** 

+0.0/+25.0 **Outlet Connection Size:** 1.000 in. Npt Base: Not included Float Type: Free

## NSN 6680-00-217-6868

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Steel, stainless
Integral Heat Source:
Not included
Maximum Working Pressure:
150.0 pounds per square inch
Inlet Connection Size:
1.000 in.Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
2.5gpm
Dial Scale Reference Pointer:
Included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Vertical
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Included
Special Features:
Protective shield
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t