NSN 6680-00-221-1050

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-221-1050

Thread Direction:
Right-hand both ends
Thread Length:
0.438 inches both ends
Tip Length:
0.688 inches first end
End Application:
6115-00-918-8494 generator set, diesel
Tongue Thickness:
0.054 inches first end and 0.063 inches first end
Core Material:
Steel, carbon
Screw Thread Series Designator:
Uns both ends
Core Diameter:
Between 0.183 inches and 0.188 inches
Thread Location:
Internal both ends
End Type:
Round keyed first end
End Connection Type:
Threaded internal both ends
Setscrew:
Not included first end
Casing Material:
Steel
Wrenching Facility Type:
Hexagon both ends
Cross Section Size And Location:
0.183 inches diameter first end and 0.188 inches diameter first end
Casing Surface Treatment:
Galvanized
Casing Length Between Ferrules:
18.000 inches
Casing Outside Diameter:
0.440 inches
Casing Protective Device Type:
Coiled spring protector
Swivel End:
Provided both ends
Enddiameter:
1.000 inches both ends

NSN 6680-00-221-1050

Flexible Shaft Assembly - Page 2 of 2



Lubrication Fitting:

Not provided both ends

Corelength:

18.000 inches

Core Rotation Direction:

Clockwise or counterclockwise

Minimum Operating Radius:

4.000 inches

Special Features:

Input end type sae marine fitting; output end type sae tach heavy fitting; ferrule and coupling nuts material brass

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T246-e