

NSN 6680-00-221-8910 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-221-8910 **Thread Class:** 2b both ends **Thread Pitch Diameters:** +0.0000 to 0.8390 inches both ends **Thread Direction:** Right-hand both ends **Overall Length:**

Wrenching Facility Outside Diameter: 0.938 inches first end

Thread Depth:

87.003 inches

0.375 inches both ends

Tip Length:

1.795 inches first end

Shank Outside Diameter:

0.500 inches first end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Diameter:

0.150 inches

Thread Location:

Internal both ends

End Type:

Square male second end

End Connection Type:

Threaded internal both ends

Setscrew:

Not included both ends

Casing Material:

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.205 inches diameter first end

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

85.3750 inches

Casing Outside Diameter:

0.445 inches

NSN 6680-00-221-8910

Flexible Shaft Assembly - Page 2 of 2



| Swivel End: |
|--------------------------|
| Not provided both ends |
| Enddiameter: |
| 1.000 inches first end |
| Lubrication Fitting: |
| Not provided both ends |
| Corelength: |
| 87.003 inches |
| Core Rotation Direction: |
| Clockwise |
| Core Removability: |
| Removable |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: T246-e