

NSN 6680-00-221-8910 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-221-8910 **Thread Class:** 2b both ends **Thread Pitch Diameters:** +0.0000 to 0.8390 inches both ends **Thread Direction:** Right-hand both ends **Overall Length:** 

**Wrenching Facility Outside Diameter:** 0.938 inches first end

**Thread Depth:** 

87.003 inches

0.375 inches both ends

Tip Length:

1.795 inches first end

**Shank Outside Diameter:** 

0.500 inches first end

**Core Material:** 

Steel

**Screw Thread Series Designator:** 

Uns first end

**Core Diameter:** 

0.150 inches

**Thread Location:** 

Internal both ends

**End Type:** 

Square male second end

**End Connection Type:** 

Threaded internal both ends

Setscrew:

Not included both ends

**Casing Material:** 

**Wrenching Facility Type:** 

Knurled surface both ends

**Cross Section Size And Location:** 

0.205 inches diameter first end

**Casing Surface Treatment:** 

Zinc coated

**Casing Length Between Ferrules:** 

85.3750 inches

**Casing Outside Diameter:** 

0.445 inches

## NSN 6680-00-221-8910

Flexible Shaft Assembly - Page 2 of 2



Swivel End:
Not provided both ends
Enddiameter:
1.000 inches first end
Lubrication Fitting:
Not provided both ends
Corelength:
87.003 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T246-e