Guided

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-225-7634

Overall Length:	
19.812 inches	
Media For Which Designed:	
Mil-h-5606 hydraulic fluid	
Inlet Connection Type:	
Threaded	
End Application:	
Awacs, e-3a aircrafts	
Integral Relief Valve:	
Not included	
Meter Type:	
Float	
Design Type:	
Case	
Unit Type:	
Mounted	
Scale Quantity:	
1	
Construction:	
Side plate	
Outlet Connection Type:	
Threaded	
Scale Marking:	
Gpm	
Scale Type:	
Direct capacity reading	
Float Quantity:	
1	
Tube Material:	
Glass	
Mounting Method:	
Flush panel	
Carrying Handle:	
Not included	
Dial Scale Marking Range:	
+0.2/+1.5	
Outlet Connection Size:	
0.375 in. Od tube size	
Base:	
Included	
Float Type:	
Cuided	

NSN 6680-00-225-7634

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Steel, stainless
Guide Type:
Beaded tube
Integral Heat Source:
Not included
Maximum Working Pressure:
150.0 pounds per square inch
Inlet Connection Size:
0.375 in. Od tube size
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
0.05gpm
Dial Scale Reference Pointer:
Included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Sight window set directly in tube, method of indicating
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t
Mil-std (military Standard):
Mil-h-5606 spec.