## NSN 6680-00-236-0710

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-236-0710 **Overall Length:** 12.500 inches Media For Which Designed: Air **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Glass **Unit Type:** Mounted **Scale Quantity: Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Direct line **Dial Scale Marking Range:** +10.0/+70.0 **Outlet Connection Size:** 0.750 in. Npt Float Type: Guided Float Material: **Brass Guide Type:** Solid rod **Integral Heat Source:** 

Not included **Maximum Working Pressure:** 200.0 pounds per square inch

## **NSN 6680-00-236-0710**Flow Rate Indicating Meter - Page 2 of 2



nlet Connection Size:
0.750 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
2 standard cu ft per min
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
ntegral Pulsation Dampener:
Not included
nlet Connection Position For Which Designed:
Vertical
Outlet Connection Position For Which Designed:
Vertical
Alarm Signal:
Not included
Special Features:
Additional scalequantity type 1; additional scale marking cfm; additional dial scale marking range 0.0 to 50.0; additional dial scale smallest
ncrement 10 cfm
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
Γ134-t