

View Online at <https://aerobasegroup.com/nsn/6680-00-331-7887>

**Thread Class:**

2b second end

**Thread Direction:**

Right-hand both ends

**Thread Length:**

0.250 inches second end

**Overall Length:**

Between 29.094 inches and 29.531 inches

**Wrenching Facility Outside Diameter:**

0.750 inches second end

**Tip Length:**

1.125 inches second end

**Shank Outside Diameter:**

0.498 inches and 0.503 inches first end

**Core Material:**

Steel

**Screw Thread Series Designator:**

Uns first end

**Core Diameter:**

0.150 inches

**Thread Location:**

Internal both ends

**End Type:**

Square male second end

**End Connection Type:**

Threaded internal both ends

**Setscrew:**

Not included both ends

**Casing Material:**

Steel

**Wrenching Facility Type:**

Knurled surface both ends

**Cross Section Size And Location:**

0.150 inches diameter and 0.155 inches diameter first end

**Torsional Deflection Rating:**

18 degrees ft lb in.

**Casing Surface Treatment:**

Zinc coated

**Casing Length Between Ferrules:**

Between 27.875 inches and 28.125 inches

**Casing Outside Diameter:**

0.445 inches

**Swivel End:**

Provided both ends

**Enddiameter:**

0.800 inches first end

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

Between 29.094 inches and 29.531 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Removable

**Fsc Application Data:**

1/tachometer group, asphalt kettle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T246-e