

View Online at <https://aerobasegroup.com/nsn/6680-00-331-7887>

Thread Class:

2b second end

Thread Direction:

Right-hand both ends

Thread Length:

0.250 inches second end

Overall Length:

Between 29.094 inches and 29.531 inches

Wrenching Facility Outside Diameter:

0.750 inches second end

Tip Length:

1.125 inches second end

Shank Outside Diameter:

0.498 inches and 0.503 inches first end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Diameter:

0.150 inches

Thread Location:

Internal both ends

End Type:

Square male second end

End Connection Type:

Threaded internal both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.150 inches diameter and 0.155 inches diameter first end

Torsional Deflection Rating:

18 degrees ft lb in.

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

Between 27.875 inches and 28.125 inches

Casing Outside Diameter:

0.445 inches

Swivel End:

Provided both ends

Enddiameter:

0.800 inches first end

Lubrication Fitting:

Not provided both ends

Corelength:

Between 29.094 inches and 29.531 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Fsc Application Data:

1/tachometer group, asphalt kettle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T246-e