

View Online at <https://aerobasegroup.com/nsn/6680-00-352-6597>

**Thread Class:**

2b first end

**Thread Direction:**

Right-hand both ends

**Thread Length:**

0.375 inches second end

**Overall Length:**

Between 192.875 inches and 193.250 inches

**Thread Depth:**

0.266 inches first end

**Tip Length:**

0.875 inches and 1.125 inches first end

**Shank Outside Diameter:**

0.500 inches first end

**Shoulder Outside Diameter:**

0.800 inches first end

**Core Material:**

Steel

**Screw Thread Series Designator:**

Uns first end

**Core Surface Treatment:**

Copper plated and tin coated

**Core Diameter:**

0.150 inches

**Thread Location:**

Internal first end

**End Type:**

Square male second end

**End Connection Type:**

Union ferrule first end

**Setscrew:**

Not included both ends

**Casing Material:**

Steel

**Cross Section Size And Location:**

0.100 inches diameter and 0.108 inches diameter second end

**Casing Surface Treatment:**

Zinc coated

**Casing Length Between Ferrules:**

Between 191.875 inches and 192.125 inches

**Casing Outside Diameter:**

Between 0.440 inches and 0.450 inches

**Swivel End:**

Not provided both ends

**Enddiameter:**

0.875 inches second end

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

Between 192.875 inches and 193.250 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Removable

**Minimum Operating Radius:**

3.000 inches

**Special Features:**

Counterclockwise core rotation direction

**Fsc Application Data:**

Speedometer group, truck chassis

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T246-e