NSN 6680-00-357-0837

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-357-0837

| Thread Class: |
|---|
| 2b both ends |
| Thread Direction: |
| Right-hand both ends |
| Overall Length: |
| Between 200.920 inches and 201.300 inches |
| Tip Length: |
| 0.620 inches and 0.880 inches first end |
| End Application: |
| Type a-532p-4 fire truck |
| Core Material: |
| Steel, spring |
| Screw Thread Series Designator: |
| Uns first end |
| Core Diameter: |
| 0.150 inches |
| End Type: |
| Square male second end |
| End Connection Type: |
| Threaded internal both ends |
| Setscrew: |
| Not included both ends |
| Casing Material: |
| Steel |
| Wrenching Facility Type: |
| Serrated surface both ends |
| Cross Section Size And Location: |
| 0.201 inches diameter and 0.205 inches diameter first end |
| Machined Feature Size: |
| 0039 in. To 0.045 in. H by 0.058 in. To 0.063 in. W drive key |
| Casing Surface Treatment: |
| Galvanized |
| Casing Length Between Ferrules: |
| 200.000 inches |
| Casing Outside Diameter: |
| 0.445 inches |
| Swivel End: |
| Not provided both ends |
| Enddiameter: |
| 1.000 inches first end |
| Lubrication Fitting: |
| Not provided both ends |
| |

NSN 6680-00-357-0837

Flexible Shaft Assembly - Page 2 of 2



Corelength:

Between 200.920 inches and 201.300 inches

Core Removability:

Removable

Minimum Operating Radius:

5.000 inches

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T246-e