

View Online at https://aerobasegroup.com/nsn/6680-00-400-3846

Rate Of Flow Transmitter - Page 1 of 2 **Terminal Quantity:** 4 **Terminal Type:** Pin contacts **Overall Length:** 6.060 inches **Overall Height:** 6.375 inches **Current Type:** Ac **Frequency Rating:** Between 30.0 hertz and 1440.0 hertz **Overall Diameter:** 2.750 inches **Attachment Feature Quantity:** 2 **Actuation Method:** Momentum type using impeller and turbine Voltage Rating: 0.030 volts **Electrical Connection Quantity:** 1 **Electrical Connection Controlling Agency:** An **Electrical Connection Identifying Number:** Ms3102a-10sl-4p or an3102a-10sl-4p **Mechanical Connection Quantity:** 2 **Mechanical Connection Size:** 2 in. Od tube size **Mechanical Connection Type:** Male flared tube **Mounting Method:** Thd male tube connections Measurement Range: +2375.0/+114000.0 pounds per hour Phase: Single **Special Features:** Extended range with 20 point calibration; 6.2 to 300 gallons/minute; flow ration 1: 48; accuracy 0.25% of reading; repeatabili type 0.02%; materials stainless steel **Fsc Application Data:**

Transmitter, rate of flow, except engine

NSN 6680-00-400-3846

Rate Of Flow Transmitter - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T145-b

