## NSN 6680-00-419-9592

Overall Length: 5.500 inches

Water

Not included

Media For Which Designed:

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-00-419-9592



**Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gal per hr Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +3.0/+30.0 **Outlet Connection Size:** 0.125 in. Npt Base: Not included Float Type: Free Float Material: Glass **Integral Heat Source:** 

## NSN 6680-00-419-9592

Flow Rate Indicating Meter - Page 2 of 2



Maximum Working Pressure:
200.0 kilograms per square centimeter
Inlet Connection Size:
0.125 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
1/4 gal per hr
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Swivel
<b>Outlet Connection Position For Which Designed:</b>
Horizontal
Horizontal  Outlet Connection Device Type:
Outlet Connection Device Type:
Outlet Connection Device Type: Swivel
Outlet Connection Device Type: Swivel Alarm Signal:
Outlet Connection Device Type: Swivel Alarm Signal: Not included
Outlet Connection Device Type: Swivel Alarm Signal: Not included Shelf Life:
Outlet Connection Device Type: Swivel Alarm Signal: Not included Shelf Life: N/a
Outlet Connection Device Type: Swivel Alarm Signal: Not included Shelf Life: N/a
Outlet Connection Device Type: Swivel Alarm Signal: Not included Shelf Life: N/a Unit Of Measure:
Outlet Connection Device Type: Swivel Alarm Signal: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: