## NSN 6680-00-442-2333

Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-442-2333 **Body Material:** Copper alloy **Maximum Operating Pressure:** 150.0 pounds per square inch Media For Which Designed: Water **Inlet Connection Type:** Threaded **Maximum Operating Temp:** 130.0 degrees fahrenheit Installation Design: Direct mount **Inlet Connection Size:** 1.250 in. lps **Measurement Unit:** Imperial gallon Scale Measurement Range: +0.0/+999999.0 **Outlet Connection Type:** Threaded **Displacement Type:** Rotary piston **Installation Location:** Any acceptable **Register Type:** Wheel **Reset Feature:** Not provided **Printing Mechanism:** Not provided **Inlet Union Connection:** Not provided **Outlet Connection Size:** 1.0in. ld **Outlet Union Connection:** Not provided **Reference Number Differentiating Characteristics:** As differentiated by inlet connection size, outlet connection size Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 6680-00-442-2333

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



D !!		
Demil	ıtarız	ation:

No

Fiig:

T134-d