

View Online at <https://aerobasegroup.com/nsn/6680-00-507-9980>

**Thread Class:**

2b both ends

**Thread Direction:**

Right-hand both ends

**Overall Length:**

139.156 inches

**Thread Depth:**

0.375 inches second end

**Tip Length:**

0.950 inches second end and 1.010 inches second end

**End Application:**

Truck, cargo, dropside, xlwb, 5-ton, 6x6 (m814, m927, m928); tank, sheridan m-551); truck, tractor, 5-ton (m818, m931); truck, wrecker, 5-ton (m936); truck, cargo, dropside, 5-ton, 6x6 (m813a1, m-923, m-925); maint facility, night sight (nsmf), tam e10227; tank, m-60 series; crane, whl, mtd

**Core Material:**

Any acceptable

**Screw Thread Series Designator:**

Uns first end

**Core Diameter:**

0.150 inches

**Thread Location:**

Internal both ends

**End Type:**

Square male second end

**Width Across Flats:**

1.000 inches first end

**End Connection Type:**

Threaded internal both ends

**Setscrew:**

Not included both ends

**Casing Material:**

Rubber and steel

**Wrenching Facility Type:**

Hexagon both ends

**Cross Section Size And Location:**

0.150 inches diameter first end and 0.153 inches diameter first end

**Casing Surface Treatment:**

Any acceptable

**Casing Length Between Ferrules:**

130.000 inches

**Casing Outside Diameter:**

Between 0.300 inches and 0.500 inches

**Casing Protective Device Type:**

Plastic cover or rubber cover

**Swivel End:**

Not provided both ends

**Enddiameter:**

1.188 inches first end

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

139.156 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Removable

**Minimum Operating Radius:**

5.000 inches

**Special Features:**

Counterclockwise core rotation direction

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T246-e