NSN 6680-00-507-9984

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-507-9984
Thread Class:
2b both ends
Thread Direction:
Right-hand both ends
Overall Length:
71.203 inches
Thread Depth:
0.375 inches second end
Tip Length:
0.790 inches first end
Core Material:
Steel
Screw Thread Series Designator:
Uns first end
Core Surface Treatment:
Cadmium plated
Core Diameter:
0.150 inches
Thread Location:
Internal both ends
End Type:
Square male second end
Width Across Flats:
1.000 inches first end
End Connection Type:
Threaded internal both ends
Setscrew:
Not included both ends
Casing Material:
Steel
Wrenching Facility Type:
Hexagon both ends
Cross Section Size And Location:
0.150 inches diameter first end
Casing Surface Treatment:
Cadmium plated
Casing Length Between Ferrules:
70.000 inches

0.688 inches

Casing Protective Device Type:

Casing Outside Diameter:

Rubber cover

NSN 6680-00-507-9984Flexible Shaft Assembly - Page 2 of 2



Swivel End:	
Not provided both ends	
Lubrication Fitting:	
Not provided both ends	
Corelength:	
71.203 inches	
Core Rotation Direction:	
Clockwise	
Core Removability:	
Removable	
Special Features:	
Counterclockwise core rotation direction; thread size: 5/8-18 first end and 7/8-18 second end	
Fsc Application Data:	
Speedometer, combat tank	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
Yes - demil/mli	
Fiig:	
T246-e	