## NSN 6680-00-525-8783

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-525-8783 **Overall Length:** 8.440 inches Media For Which Designed: Water **Inlet Connection Type:** Threaded **End Application:** Brooks instrument div emerson electric co, an/apm-373 radar test set **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Side plate **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass, borosilicate **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.2/+2.6 **Outlet Connection Size:** 0.375 in. Npt Base: Not included

Float Type: Guided

## NSN 6680-00-525-8783

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Steel, corrosion resisting, type 316 per qq-s-766
Guide Type:
Solid rod
Integral Heat Source:
Not included
Maximum Working Pressure:
200.0 pounds per square inch
Inlet Connection Size:
0.375 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
6mm
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Swivel
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Swivel
Alarm Signal:
Not included
Special Features:
Protective shield; stainless steel end fittings
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t