

NSN 6680-00-526-6783 Liquid Volumetric Positive Displacement Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-00-526-6783 **Body Material:** Bronze **Maximum Operating Pressure:** Any acceptable Media For Which Designed: Water, cold **Inlet Connection Type:** Threaded **Maximum Operating Temp:** Any acceptable Installation Design: Direct mount **Inlet Connection Size:** 0.750 in. lps **Measurement Unit:** Us gallon **Scale Measurement Range:** +0.0 to 10.0 **Outlet Connection Type:** Threaded **Smallest Increment Indicated:** 0.25 **Displacement Type:** Disk **Installation Location:** Right hand side **Liquid Flow Rate:** 30.0 gallons per minute

Register Type:

Dial w/pointer or wheel

Reset Feature:

Not provided

Printing Mechanism:

Not provided

Inlet Union Connection:

Provided

Outlet Connection Size:

0.750 in. lps

Outlet Union Connection:

Provided

Special Features:

Additional scale measurement range 0.0 to 999999.0

NSN 6680-00-526-6783

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T134-d