## NSN 6680-00-526-6785

Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-526-6785 **Body Material:** Bronze **Maximum Operating Pressure:** 125.0 pounds per square inch Media For Which Designed: Water, cold **Inlet Connection Type:** Threaded Installation Design: Direct mount **Inlet Connection Size:** 1.000 in. lps **Measurement Unit:** Us gallon **Scale Measurement Range:** +0.0/+10.0 **Outlet Connection Type:** Threaded **Smallest Increment Indicated:** 0.25 **Displacement Type:** Disk Installation Location: Right hand side **Liquid Flow Rate:** 50.0 gallons per minute **Register Type:** Dial w/pointer or wheel **Reset Feature:** Not provided **Printing Mechanism:** Not provided **Inlet Union Connection:** Provided **Outlet Connection Size:** 1.000 in. lps **Outlet Union Connection:** Provided **Special Features:** Additional scale measurement range 0.0 to 99999.0

Additional so **Shelf Life:** 

N/a

## NSN 6680-00-526-6785

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

T134-d