

View Online at <https://aerobasegroup.com/nsn/6680-00-528-4682>

**Thread Class:**

2b first end

**Thread Direction:**

Right-hand both ends

**Thread Length:**

0.250 inches second end

**Overall Length:**

64.000 inches

**Wrenching Facility Outside Diameter:**

0.938 inches first end

**Thread Depth:**

0.250 inches first end

**Tip Length:**

0.562 inches and 0.625 inches first end

**Shank Outside Diameter:**

0.625 inches second end

**Core Material:**

Steel

**Screw Thread Series Designator:**

Uns first end

**Core Diameter:**

0.130 inches

**Thread Location:**

Internal first end

**End Type:**

Square male second end

**Width Across Flats:**

0.875 inches second end

**End Connection Type:**

Threaded internal first end

**Setscrew:**

Not included both ends

**Casing Material:**

Steel

**Wrenching Facility Type:**

Knurled surface first end

**Cross Section Size And Location:**

0.201 inches diameter and 0.205 inches diameter first end

**Torsional Deflection Rating:**

25 degrees ft-lb in.

**Casing Surface Treatment:**

Galvanized

**Casing Length Between Ferrules:**

63.125 inches

**Casing Outside Diameter:**

0.243 inches

**Swivel End:**

Provided both ends

**Enddiameter:**

1.000 inches both ends

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

64.000 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Removable

**Fsc Application Data:**

Speedometer group, dump truck

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T246-e