

View Online at <https://aerobasegroup.com/nsn/6680-00-528-4682>

Thread Class:

2b first end

Thread Direction:

Right-hand both ends

Thread Length:

0.250 inches second end

Overall Length:

64.000 inches

Wrenching Facility Outside Diameter:

0.938 inches first end

Thread Depth:

0.250 inches first end

Tip Length:

0.562 inches and 0.625 inches first end

Shank Outside Diameter:

0.625 inches second end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Diameter:

0.130 inches

Thread Location:

Internal first end

End Type:

Square male second end

Width Across Flats:

0.875 inches second end

End Connection Type:

Threaded internal first end

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface first end

Cross Section Size And Location:

0.201 inches diameter and 0.205 inches diameter first end

Torsional Deflection Rating:

25 degrees ft-lb in.

Casing Surface Treatment:

Galvanized

Casing Length Between Ferrules:

63.125 inches

Casing Outside Diameter:

0.243 inches

Swivel End:

Provided both ends

Enddiameter:

1.000 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

64.000 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Fsc Application Data:

Speedometer group, dump truck

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e