

View Online at <https://aerobasegroup.com/nsn/6680-00-528-4915>

**Thread Class:**

2b second end

**Thread Direction:**

Right-hand both ends

**Thread Length:**

0.375 inches second end

**Groove Width:**

0.188 inches second end

**Overall Length:**

101.266 inches

**Tip Length:**

0.828 inches first end

**Shank Outside Diameter:**

0.500 inches both ends

**Shoulder Outside Diameter:**

0.875 inches first end

**Core Material:**

Steel

**Screw Thread Series Designator:**

Uns first end

**Core Surface Treatment:**

Galvanized

**Core Diameter:**

0.203 inches

**Distance From End To Groove Center:**

1.000 inches first end

**Thread Location:**

Internal both ends

**End Type:**

Square male second end

**Width Across Flats:**

0.750 inches second end

**End Connection Type:**

Threaded internal both ends

**Groove Quantity:**

2 second end

**Setscrew:**

Not included both ends

**Casing Material:**

Steel

**Wrenching Facility Type:**

Hexagon both ends

**Cross Section Size And Location:**

0.203 inches diameter first end

**Casing Surface Treatment:**

Galvanized

**Casing Length Between Ferrules:**

100.000 inches

**Casing Outside Diameter:**

0.469 inches

**Casing Protective Device Type:**

Coiled spring protector and rubber cover

**Swivel End:**

Not provided both ends

**Enddiameter:**

0.625 inches second end

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

101.203 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Removable

**Minimum Operating Radius:**

3.500 inches

**Fsc Application Data:**

Speedometer

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T246-e