

View Online at <https://aerobasegroup.com/nsn/6680-00-528-4915>

Thread Class:

2b second end

Thread Direction:

Right-hand both ends

Thread Length:

0.375 inches second end

Groove Width:

0.188 inches second end

Overall Length:

101.266 inches

Tip Length:

0.828 inches first end

Shank Outside Diameter:

0.500 inches both ends

Shoulder Outside Diameter:

0.875 inches first end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Surface Treatment:

Galvanized

Core Diameter:

0.203 inches

Distance From End To Groove Center:

1.000 inches first end

Thread Location:

Internal both ends

End Type:

Square male second end

Width Across Flats:

0.750 inches second end

End Connection Type:

Threaded internal both ends

Groove Quantity:

2 second end

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.203 inches diameter first end

Casing Surface Treatment:

Galvanized

Casing Length Between Ferrules:

100.000 inches

Casing Outside Diameter:

0.469 inches

Casing Protective Device Type:

Coiled spring protector and rubber cover

Swivel End:

Not provided both ends

Enddiameter:

0.625 inches second end

Lubrication Fitting:

Not provided both ends

Corelength:

101.203 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

3.500 inches

Fsc Application Data:

Speedometer

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T246-e