

	<b>)-00-528-4916</b> Assembly - Page 1 of 2	AeroBase Group
View Online at http:	s://aerobasegroup.com/nsn/6680-00-528-4916	
Thread Pitch Diam	eters:	
+0.8400 to 0.8450 i	nches both ends	
Thread Direction:		
Right-hand both en	ds	
Groove Width:		
0.125 inches both	ends	
Overall Length:		
28.609 inches		
Wrenching Facility	Outside Diameter:	
1.000 inches both	ends	
Thread Depth:		

Thread Depth:

0.375 inches both ends

Tip Length:

0.656 inches first end

#### **Shank Outside Diameter:**

0.688 inches both ends

**Core Material:** 

Steel

### **Screw Thread Series Designator:**

Uns both ends

**Core Diameter:** 

0.150 inches

## **Distance From End To Groove Center:**

0.062 inches both ends

**Thread Location:** 

Internal both ends

End Type:

Square male second end

## **End Connection Type:**

Circumferentially grooved both ends

**Groove Quantity:** 

1 both ends

Setscrew:

Not included both ends

**Casing Material:** 

Steel

### Wrenching Facility Type:

Knurled surface both ends

## **Cross Section Size And Location:**

0.152 inches diameter first end

### **Casing Surface Treatment:**

Galvanized

# **NSN 6680-00-528-4916**Flexible Shaft Assembly - Page 2 of 2



Casing Length Between Ferrules:
27.500 inches
Casing Outside Diameter:
0.438 inches
Casing Protective Device Type:
Coiled spring protector
Swivel End:
Provided both ends
Enddiameter:
1.000 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
27.594 inches
Core Rotation Direction:
Clockwise or counterclockwise
Core Removability:
Removable
Special Features:
Second end cross section size and location 0.185 in. Sq
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
Г246-е