

View Online at <https://aerobasegroup.com/nsn/6680-00-528-9471>

Thread Class:

2b second end

Thread Direction:

Right-hand both ends

Thread Length:

0.380 inches both ends

Overall Length:

25.000 inches

Tip Length:

0.560 inches first end

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Surface Treatment:

Any acceptable

Core Diameter:

0.190 inches

Thread Location:

Internal first end

End Type:

Round keyed first end

Width Across Flats:

0.940 inches first end

End Connection Type:

Threaded internal first end

Setscrew:

Not included both ends

Casing Material:

Any acceptable

Wrenching Facility Type:

Octagon first end

Cross Section Size And Location:

0.530 inches diameter first end

Machined Feature Size:

0.072 in. W by 0.880 in. Lg slot

Casing Surface Treatment:

Any acceptable

Casing Length Between Ferrules:

24.000 inches

Casing Protective Device Type:

Braided wire shield and rubber cover

Swivel End:

Not provided both ends

Lubrication Fitting:

Not provided both ends

Corelength:

24.875 inches

Core Rotation Direction:

Clockwise

Core Removability:

Nonremovable

Minimum Operating Radius:

6.000 inches

Special Features:

Counterclockwise core rotation direction

Specification Or Standard:

No. An5533-5 type

Fsc Application Data:

Tachometer generator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e