

View Online at <https://aerobasegroup.com/nsn/6680-00-529-0274>

Thread Class:

2b or 2 first end

Thread Direction:

Right-hand both ends

Thread Length:

0.313 inches first end

Overall Length:

56.281 inches

Wrenching Facility Outside Diameter:

0.750 inches second end

Thread Depth:

0.344 inches second end

Tip Length:

0.828 inches first end

Shank Outside Diameter:

0.531 inches second end

Shoulder Outside Diameter:

0.750 inches first end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Surface Treatment:

Zinc coated

Core Diameter:

0.203 inches

Thread Location:

Internal both ends

End Type:

Square male second end

Width Across Flats:

1.000 inches first end

End Connection Type:

Union ferrule first end

Setscrew:

Not included both ends

Casing Material:

Rubber and steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.203 inches diameter first end

Torsional Deflection Rating:

15 degrees ft-lb in. Torsional deflection rating

Casing Surface Treatment:

Galvanized

Casing Length Between Ferrules:

55.000 inches

Casing Outside Diameter:

0.517 inches

Casing Protective Device Type:

Rubber cover

Swivel End:

Not provided second end

Overall End Size:

Second end: 5/8 in. Across flats

Lubrication Fitting:

Not provided both ends

Corelength:

56.203 inches

Core Rotation Direction:

Clockwise or counterclockwise

Core Removability:

Removable

Minimum Operating Radius:

5.000 inches

Special Features:

2.5 lb torsion strength in unwinding direction

Fsc Application Data:

Speedometer, tractor, towing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e