## NSN 6680-00-530-2621

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-530-2621 **Overall Length:** 20.875 inches Media For Which Designed: Water, salt **Inlet Connection Type:** Threaded Dial Range: +0.0/+285.0 **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gal per hr Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +25.0/+275.0 **Outlet Connection Size:** 0.750 in. lps Base: Not included

Float Type: Guided

## NSN 6680-00-530-2621

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Nickel copper
Guide Type:
Solid rod
Integral Heat Source:
Not included
Maximum Working Pressure:
300.0 pounds per square inch
Inlet Connection Size:
0.750 in. lps
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
5 gal per hr
Dial Scale Reference Pointer:
Not included
Spinning Float:
Included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Swivel
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Swivel
Alarm Signal:
Not included
Special Features:
Plastic safety shield
Reference Number Differentiating Characteristics:
Serial no. 7805a1181a1
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t