NSN 6680-00-563-8040

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-563-8040 **Thread Class:** 2b second end **Thread Direction:** Right-hand both ends Thread Length: 0.438 inches both ends **Overall Length:** 29.031 inches Tip Length: 0.625 inches first end **Core Material:** Steel **Screw Thread Series Designator:** Uns first end **Core Surface Treatment:** Copper and tin salts **Core Diameter:** 0.130 inches **Thread Location:** Internal both ends **End Type:** Square male second end **End Connection Type:** Threaded internal both ends Setscrew: Not included both ends **Casing Material:** Steel **Cross Section Size And Location:** 0.152 inches diameter first end **Torsional Deflection Rating:** 1/8 degrees ft-lb in winding direction, 25 degrees ft-lb in unwinding direction **Casing Surface Treatment:** Zinc coated **Casing Length Between Ferrules:** 28.000 inches **Casing Outside Diameter:**

0.245 inches Swivel End: Provided first end **Enddiameter:** 1.000 inches first end

NSN 6680-00-563-8040

Flexible Shaft Assembly - Page 2 of 2



Lubrication Fitting:
Not provided both ends
Corelength:
29.031 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
3.000 inches
Special Features:
Counterclockwise core rotation direction, torsion strength winding direction 17.0 lbs.Thread size is 5/8-18 and 7/8-18.
Fsc Application Data:
Tachometer, truck mtd cleaning-de-icing-decontaminating fluid spraying unit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T246-e