NSN 6680-00-580-1891

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-00-580-1891



Overall Length: 12.310 inches Media For Which Designed: 50 pct ethylene glycol, 50 pct water solution **Inlet Connection Type:** Hose nipple **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Glass **Unit Type:** Mounted **Scale Quantity: Outlet Connection Type:** Hose nipple Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Direct line **Dial Scale Marking Range:** +1.0/+6.8 **Outlet Connection Size:** 1 in. Hose nipple Float Type: Guided Float Material: Steel, stainless **Guide Type:** Solid rod **Integral Heat Source:** Not included **Maximum Working Pressure:** 100.0 pounds per square inch

NSN 6680-00-580-1891

Flow Rate Indicating Meter - Page 2 of 2



Inlet Connection Size:
1 in. Hole nipple
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
0.25 gpm
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Vertical
Outlet Connection Position For Which Designed:
Vertical
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Acqw, cpzd, cpzp, acrn, acrl, acrm arth, bhcm, cpzr, bhcs, bhct, bhcw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t